

Allison Transmission Filter Addendum

2007 Dynasty, Signature, The Executive, Camelot, Diplomat, and Knight

The information printed here reflects product design, fabrication, and component parts at the date of printing. The manufacturer reserves the right, at any time, to make changes in product design or material or component specifications as its sole option, without notice. This includes the substitution of components of a different brand or trade name, which will result in comparable performance. All information printed in this document is subject to change after the date of printing. Due to product improvements, changes during the model year and/or transcription errors that may occur, information represented within the owner's manual and/or this document may not be accurate at the time of your purchase. Please confirm any information with your dealer.

The following information supercedes previous information and applies certain model motorhomes equipped with a Roadmaster Chassis.

©Monaco Coach Corporation. All rights reserved. All other trademarks or registered trademarks are property of their respective holders. Brand name products of other companies mentioned in this addendum are not endorsed by Monaco Coach Corporation.

The information in Section 10 – Chassis Transmission Fluids and Filters has changed. This change affects the following:

Monaco: 2007 Dynasty pg. 268, 2007 Signature pg. 251, 2007 The Executive pg 250, 2007 Camelot pg. 229, 2007 Diplomat pg. 216 and 2007 Knight pg. 209.


The maintenance schedule affecting the Allison MH 3000 and MH 4000 series transmission regarding initial Main filter replacement interval has changed. The mileage requirement to change the Main filter at the first 5000 miles has been superseded to reflect the following information.

TRANSMISSION FLUID AND FILTERS

The transmission is filled with TranSynd™ synthetic transmission fluid at the factory. TranSynd™ synthetic transmission fluid extends service intervals. A small tag has been attached to the dipstick identifying that the transmission is filled with TranSynd™ synthetic transmission fluid.

Fluid and Filter Change Interval:

The transmission has two filters: a Main filter and a Lube filter. Beginning approximately July 2006, MH3000 transmissions built prior to serial number 6510670912 and MH4000 transmissions built prior to 6610205144 require the Main filter to be changed at the first 5,000 miles. MH3000 and MH4000 transmissions with subsequent serial numbers are to follow the service intervals listed in the transmission OEM (Original Equipment Manufacturers) manual. Fluid and filters may require changing earlier than recommended in the transmission OEM manual depending on the severity of operating conditions. Fluid must also be changed whenever there is evidence of dirt or high temperature operation as indicated by discoloration, strong odor or fluid analysis. Local conditions, severity of operation or duty cycle will dictate more or less frequent service intervals.



CAUTION:

Fluid and filter service interval is shortened if Dexron III® transmission fluid is mixed with TranSynd™ TES295 synthetic transmission fluid. Refer to OEM transmission manual for further information.

NOTE:

Be sure to retain the receipt for proof of the initial Main filter replacement for those transmissions built prior to above serial numbers. Refer to the Allison transmission owner's manual or contact an authorized Allison service center for service intervals.



M O N A C O®

Monaco Coach Corporation
91320 Coburg Industrial Way
Coburg, OR 97408
800-634-0855
www.monacocoach.com

Warranty/Technical Support
Toll Free 877-466-6226